

# XLT-30

## ACOUSTICAL LEAK DETECTOR



Fisher's XLT-30 leak detector is built to perform and priced to compete. With advanced electronic amplification and filtering, an all tactile keypad along with an easy to read digital display and notch feature, which allows independent suppression of outside interfering noise, the XLT-30 proves its worth again and again.

Fisher's XLT-30 is available in 3 options: Option A with a Bigfoot Hydrophonic probe sensor, Option B with the New Multi-Sensor & Option C with the Littlefoot Hydrophonic Probe.

In the Fisher tradition, the XLT-30 is affordable, tough, and simple to use while providing maximum performance. A two year limited warranty comes standard with the unit.

### Features

- Detects and pinpoints liquid leaks in pipes
- Notch filter for external noise suppression
- Ultra low amplifier noise
- Peak hold feature on LCD bargraph for sound comparison
- Automatic limiter system to enhance weak noise sources
- Tactile keypad & digital display, backlit for low light usage
- Increased response in poor sound conductors
- Shielded sensor for reduced response to outside noise
- Improved headset for clearer sound response
- Automatic battery test and monitoring  
Operates on two 9 volt batteries



200 W. Willmott Rd., Los Banos, CA 93635-5501

T 209.826.3292 F 209.826.0416 [www.fisherlab.com](http://www.fisherlab.com) [info@fisherlab.com](mailto:info@fisherlab.com)

Fisher Labs has been serving the demanding needs of the utility industry with innovative locating solutions - Since 1931. From pipe & cable locators, valve & box locators, sound & leak detectors to water level indicators, Find it... with Fisher!

# XLT-30 specifications



Specifications subject to change without notice.

## Operating frequency Range

All pass mode .....60Hz - 6kHz

Filter mode .....60Hz - 2.4kHz

## Filter Types:

.....Independent notch filter

.....Lowpass, Highpass or Bandpass

Gain .....95dB

## Output Indications:

Audio.....High performance headphones (64 ohms)

Visual.....LCD bargraph and 2-digit numeric display

Battery Test.....Automatic

Battery Type.....Two 9 Volt alkaline

Battery Life.....50 Hours (approximate)

## NEW MULTI-SENSOR

### Option B



**Little Foot & Hydrophonic Sensor  
Option C**



**Big Foot & Hydrophonic Probe Sensor  
Option A**

### Option A: Big Foot and Hydrophonic Probe Sensor

Fisher's trusted Big Foot sensor has a proven track record locating leaks. This heavy-duty sensor is great for finding leaks without direct contact such as beneath asphalt or concrete slabs. The Hydrophonic Probe works outstanding when a direct contact can be made

### Option B: NEW MULTI-SENSOR

Fisher's new MULTI-SENSOR has superior leak detection capabilities. In an extremely compact design, Fisher has achieved higher performance, improved audio clarity, improved sensor electronics, and better sensitivity to leaks with less background noise – all with heavy duty characteristics of the trusted Big Foot. The MULTI-SENSOR is used for both the ground microphone and direct contact applications – the one sensor that does it all. Fisher's NEW XLT-30 MULTI-SENSOR combo sets the new standard for leak detection. .

### Option C: Little Foot and Hydrophonic Probe Sensor

Fisher's reliable Little Foot is an ultra sensitive ground microphone about the size of a computer "mouse." Excellent for leak locating on interior walls and surfaces. The Hydrophonic Probe works outstanding when a direct contact can be made.

## 2-Year Warranty

Fisher warrants the XLT-30 to be free of defects in materials and workmanship when it is shipped from the factory. The terms of this warranty are fully explained in a warranty registration card that accompanies the instrument. Complete factory and field service facilities support the warranty.

\*Warranty may vary outside the U.S. See your distributor for details.

## Ordering Information

### US, Mexico & Canadian Customers Contact:

#### FISHER LABS

200 W. Willmott Rd., Los Banos, CA 93635-5501

T 209.826.3292 F 209.826.0416 info@fisherlab.com  
www.fisherlab.com

### All Other Countries Contact:

#### Export Department

282 State Street, North Haven, CT 06473 USA,

T 203.288.1638 F 203.287.8099  
email: fisher@exportdept.com

